

# 14 MPa and 1.4 MPa PPC4E Demo Kits

## P/N 3934699 and P/N 3934702

### **Instruction Sheet**

14 MPa Demo kit (P/N 3934699) contents:

DESCRIPTION	QTY	PART NO.
Demo Kit Transit Case	1	3984452
PPC4 Transit Case	1	3338097
SPLT, self purging liquid trap, for PPC	1	3069823
2000 psi digital pressure gauge	1	3984160
30 psi analog pressure gauge	1	3984201
Cable assembly, DB9M x F	1	2758335
36 in. test hose assembly, 2500 psi	1	3984857
72 in. supply hose assembly, 2500 psi	1	3984869
Swivel adaptor, $1/4$ in $\times$ $1/8$ in. NPT female	1	3984825
Reducer, 1/4 in. to 1/8 in. NPT	1	1811842
Adaptor, 1/4 in. NPT male x 1/4 in. tube	1	3863458
Elbow, 1/4 in. tube	1	3867817

The 14 MPa PPC4E demo kit includes UUT (unit under test) pressure gauges with ranges selected for use with PPC4EX 14M pressure controller/calibrator.

The demo kit connections and gauges should be installed with the controller/calibrator and pressure supply as illustrated below.

Pneumatic connections that will be frequently disconnected are o-ring type quick connectors which can be connected without thread tape, sealant or tools. The traditional pipe thread and tube fittings in the kit can remain connected during transport, so that all of the connections required for a demonstration can be quickly connected by hand. Separate adaptors may be needed to connect to local pressure supply.

#### Marning

Flexible pressure hoses in this kit have maximum operating pressure of 17 MPa (2500 psi).




Figure 1: 14 MPa PPC4E Demo Kit Assembly

#### 1.4 MPa Demo Kit (P/N 3934702) contents:

DESCRIPTION	QTY	PART NO.
Demo Kit Transit Case	1	3984452
PPC4 Transit Case	1	3338097
SPLT, self purging liquid trap, for PPC	1	3069823
200 psi digital pressure gauge	1	3984172
5 psi analog pressure gauge	1	3984220
Cable assembly, DB9 M x F	1	2758335
36 in. test hose assembly, 2500 psi	1	3984857
72 in. supply hose assembly, 2500 psi	1	3984869
Swivel adaptor, 1/4 in. x 1/8 in. NPT female	1	3984825
Reducer, 1/4 in. to 1/8 in. NPT	1	1811842
Adaptor, 1/4 in. NPT male x 1/4 in. tube	1	3863458
Elbow, 1/4 in. tube	1	3867817
1/4 in. NPT male hex nipple	1	3132779

# The 1.4 MPa PPC4E demo kit includes UUT (unit under test) pressure gauges with ranges selected for use with PPC4EX 1.4M pressure controller/calibrator.

The demo kit connections and gauges should be installed with the controller/calibrator and pressure supply as illustrated below.

Pneumatic connections that will be frequently disconnected are o-ring type quick connectors which can be connected without thread tape, sealant or tools. The traditional pipe thread and tube fittings in the kit can remain connected during transport, so that all of the connections required for a demonstration can be quickly connected by hand. Separate adaptors may be needed to connect to local pressure supply.

#### 

Flexible pressure hoses in this kit have maximum operating pressure of 17 MPa (2500 psi).




Figure 2: 1.4 MPa PPC4E Demo Kit Assembly

Fluke. Keeping your world up and running.®

Fluke Calibration PO Box 9090 Everett, WA 98206 U.S.A.

Fluke Europe B.V. PO Box 1186, 5602 BD Eindhoven, The Netherlands For more information call: In the U.S.A. (800) 443-5853 or Fax (425) 446-5116 In Europe/M-East/Africa +31 (0) 40 2675 200 or Fax +31 (0) 40 2675 222 In Canada (800)-36-FLUKE or Fax (905) 890-6866

From other countries: +1 (425) 446-5500 or

Fax +1 (425) 446-5116

Web access: http://www.fluke.com

©2011 Fluke Corporation. Specifications subject to change without notice. Printed in U.S.A. 3/2011 3986408A D-EN-N

Modification of this document is not permitted without written permission from Fluke Corporation.