

FLUKE®

Calibration

Oscilloscope Calibration Options for **55XX Series Multi-Product Calibrators**

Extended Specifications

These specifications apply to the 5520A-SC1100, 5500A-SC600 and 5500A-SC300 Oscilloscope Calibration Options. For general specifications, see the Extended Specifications for the individual calibrator of interest (downloadable from the Fluke Calibration web site or available from your Fluke Calibration representative). The specifications are valid when the calibrator is operated under the conditions specified in the operator manual, and has completed a warm-up period of at least twice the length of time the calibrator was powered off, up to a maximum of 30 minutes.

The 5520A-SC1100, with 1100 MHz bandwidth, can be installed in a 5522A calibrator. The 5500A-SC600, with 600 MHz bandwidth, can be installed in any 55XX Series Multi-Product Calibrator. The 300 MHz option, the 5500A-SC300, is only compatible with the 5502A calibrator.



Voltage Function Specifications

5520A-SC1100 and 5500A-SC600

Volt Function		DC Signal		Square Wave Signal ¹	
Load		Into 50 Ω	Into 1 MΩ	Into 50 Ω	Into 1 MΩ
Amplitude Characteristics					
Range		0 V to ± 6.6 V	0 V to ± 130 V	± 1 mV to ± 6.6 V p-p	± 1 mV to ± 130 V p-p
Resolution		Resolution			
Range 1 mV to 24.999 mV 25 mV to 109.99 mV 110 mV to 2.1999 V 2.2 V to 10.999 V 11 V to 130 V		1 μV 10 μV 100 μV 1 mV 10 mV			
Adjustment range		Continuous			
1-year absolute uncertainty, tcal ± 5 °C		± (0.25 % of output + 40 μV)	± (0.05 % of output + 40 μV)	± (0.25 % of output + 40 μV)	± (0.1 % of output + 40 μV) ²
Sequence		1-2-5 (e.g., 10 mV, 20 mV, 50 mV)			
Square Wave Frequency Characteristics					
Range		10 Hz to 10 kHz			
1-year absolute uncertainty, tcal ± 5 °C		± (2.5 ppm of setting)			
Typical aberration (from 50 % of leading/trailing edge) 25 mV to 130 V: within 4 μs 10 mV to 25 mV: within 8 μs 1 mV to 10 mV: within 14 μs		< (0.5 % of output + 100 μV)			

¹Positive or negative, zero referenced square wave.

²Above 1 kHz, ± (0.25 % of output + 40 μV). Assumes connectors and cables are in good condition.

5500A-SC300

Volt Function		DC Signal		Square Wave Signal ¹	
Load		Into 50 Ω	Into 1 MΩ	Into 50 Ω	Into 1 MΩ
Amplitude range		0 V to ± 2.2 V	0 V to ± 33 V	± 1.8 mV to ± 2.2 V p-p	± 1.8 mV to ± 105 V p-p
1-year absolute uncertainty, tcal ± 5 °C		± (0.25 % of output + 100 μV)			
Sequence		1-2-5 (e.g., 10 mV, 20 mV, 50 mV)			
Frequency range		10 Hz to 10 kHz			

¹Positive or negative, zero referenced square wave.

Edge Function Specifications

5520A-SC1100 and 5500A-SC600

Edge Characteristics into 50 Ω		1-Year Absolute Uncertainty, tcal ± 5 °C
Amplitude		
Rise time	< 300 ps	+ 0/-100 ps
Range (p-p)	5.0 mV to 2.5 V	± (2 % of output + 200 μV)
Resolution	4 digits	
Adjustment range	± 10 % around each sequence value (indicated below)	
Sequence values	5 mV, 10 mV, 25 mV, 50 mV, 60 mV, 80 mV, 100 mV, 200 mV, 250 mV, 300 mV, 500 mV, 600 mV, 1 V, 2.5 V	
Other Edge Characteristics		
Frequency range	1 kHz to 10 MHz ¹	± (2.5 ppm of setting)
Frequency range	≤ 300 ps ¹	(+ 0 ps/-100 ps)
Typical jitter, edge to trigger	< 5 ps [p-p]	
Leading edge aberrations ²	within 2 ns from 50 % of rising edge]	< (3 % of output + 2 mV)
	2 ns to 5 ns	< (2 % of output + 2 mV)
	5 ns to 15 ns	< (1 % of output + 2 mV)
	after 15 ns	< (0.5 % of output + 2 mV)
Typical duty cycle	45 % to 55 %	
Tunnel diode pulse drive	Square wave at 100 Hz to 100 kHz, with variable amplitude of 60 V to 100V p-p	

¹Frequency range above 2 MHz has rise time specification ≤ 350 ps.

²Below 250 mV aberrations are typical.

5500A-SC300

Edge Characteristics into 50 Ω		1-Year Absolute Uncertainty, tcal ± 5 °C
Amplitude range (p-p)	4.5 mV to 2.75 V	± (2 % of output + 200 μV)
Frequency range	1 kHz to 1 MHz	± (25 ppm of setting + 15 MHz)
Rise time	≤ 1 ns	
Typical jitter, edge to trigger	< 5 ps (p-p)	
Leading edge aberrations	Within 10 ns	< (2 % of output + 2 mV)
	10 to 30 ns	< (1 % of output + 2 mV)
	After 30 ns	< (0.5 % of output + 2 mV)
Typical duty cycle	45 % to 55 %	

Leveled Sinewave Function Specifications

5520A-SC1100 (> 600 MHz)

Characteristics into 50 Ω	Frequency Range	
	50 kHz (reference)	600 MHz to 1.1 GHz
Amplitude Characteristics		
Range	5 mV to 3.5 V	
Resolution	< 100 mV: 3 digits; ≥ 100 mV: 4 digits	
Adjustment Range	Continuously Adjustable	
1-year absolute uncertainty, tcal ± 5 °C	± (2 % of output + 300 μV)	± (7 % of output + 300 μV)
Flatness (relative to 50 MHz) ¹	not applicable	± (5 % of output + 100 μV)
Short-term amplitude stability	≤ 1 % ²	
Frequency Characteristics		
Resolution	100 kHz	
1-year absolute uncertainty, tcal ± 5 °C	± 2.5 ppm	
Distortion Characteristics		
2 nd harmonic	≤ -33 dBc	
3 rd and higher harmonic	≤ -38 dBc	

¹As measured near oscilloscope bandwidth frequency.

²Within one hour after reference amplitude setting, provided temperature varies no more than ± 5 °C.

5520A-SC1100 and 5500A-SC600

Leveled Sine Wave Characteristics into 50	Frequency Range			
	50 kHz (Reference)	50 kHz to 100 MHz	100 MHz to 300 MHz	300 MHz to 600 MHz
Amplitude				
Range (p-p)	5 mV to 5.5 V			
1-year absolute uncertainty, tcal ± 5 °C	± (2 % of output + 300 μV)	± (3.5 % of output + 300 μV)	± (4 % of output + 300 μV)	± (6 % of output + 300 μV)
Flatness (relative to 50 kHz) ¹	Not applicable	± (1.5 % of output + 100 μV)	± (2 % of output + 100 μV)	± (4 % of output + 100 μV)
Short-term amplitude stability	≤ 1 % ²			
Frequency				
Resolution	10 kHz			
1-year absolute uncertainty, tcal ± 5 °C	± 2.5 ppm			
Distortion				
2 nd harmonic	≤ -33 dBc			
3 rd and higher harmonics	≤ -38 dBc			

¹As measured near oscilloscope bandwidth frequency.

²Within one hour after reference amplitude setting, provided temperature varies no more than ± 5 °C.

5500A-SC300

Leveled Sine Wave Characteristics into 50 Ω	Frequency Range		
	50 kHz (Reference)	50 kHz to 100 MHz	100 MHz to 300 MHz ¹
Amplitude			
Range (p-p)	5 mV to 5.5 V ¹		
1-year absolute uncertainty, tcal ± 5 °C	± (2 % of output + 200 μV)	± (3.5 % of output + 300 μV)	± (4 % of output + 300 μV)
Flatness (relative to 50 kHz) ¹	Not applicable	± (1.5 % of output + 100 μV)	± (2 % of output + 100 μV)
Short-term amplitude stability	≤ 1 % ²		
Frequency			
Resolution	10 kHz		
1-year absolute uncertainty, tcal ± 5 °C	± 2.5 ppm		
Distortion			
2 nd harmonic	≤ -33 dBc		
3 rd and higher harmonics	≤ -38 dBc		

¹Extended frequency range to 350 MHz is provided, but flatness is not specified. Amplitude is limited to 3 V for frequencies above 250 MHz.

²Within one hour after reference amplitude setting, provided temperature varies no more than ± 5 °C.

Time Marker Function Specifications

5520A-SC1100 and 5500A-SC600

Time Marker into 50 Ω ¹	5 s to 50 ms	20 ms to 100 ns	50 ns to 20 ns	10 ns	5 ns to 2 ns
1-year absolute uncertainty, tcal ± 5 °C ²	± (25 + t* X 1000) ppm	± 2.5 ppm	± 2.5 ppm	± 2.5 ppm	± 2.5 ppm
Wave shape	Spike or square	Spike, square, 20 %-pulse	Spike or square	Square or sine	Sine
Typical jitter (p-p)	< 10 ppm	< 1 ppm	< 1 ppm	< 1 ppm	< 1 ppm
Sequence	5-2-1 from 5 s to 2 ns (e.g., 500 ms, 200 ms, 100 ms)				

¹Output amplitude > 1 V pk.

²Time marker uncertainty is ± 50 ppm when measured off of cardinal points.

*t = time in seconds.

5500A-SC300

Time Marker into 50 Ω ¹	5 s to 100 μs	50 μs to 2 μs	1 μs to 20 ns	10 ns to 2 ns
1-year absolute uncertainty, tcal ± 5 °C	± (25 + t* X 1000) pmm	± (25 + t* X 15000) pmm	± 25 ppm	± 25 ppm
Wave shape	Pulsed sawtooth	Pulsed sawtooth	Pulsed sawtooth	Sine
Sequence	5-2-1 from 5 s to 2 ns (e.g., 500 ms, 200 ms, 100 ms)			

¹Typical amplitude > 1 V

*t = time in seconds.

Trigger Functions 5520A-SC1100, 5500A-SC600 and 5500A-SC300

Available for edge and time marker functions (volt, pulse and video are available for 5520A-SC1100 and 5500A-SC600 only).

Wave Generator Function Specifications

5520A-SC1100, 5500A-SC600 and 5500A-SC300

Wave Generator Characteristics	Square Wave, Sine Wave, and Triangle Wave into 50 Ω or 1 MΩ
Amplitude	
Range	Into 1 MΩ: 1.8 mV to 55 V p-p Into 50 Ω: 1.8 mV to 2.5 V p-p (5520A-SC1100 and 5500A-SC600) Into 50 Ω: 1.8 mV to 2.2 V p-p (5500A-SC300)
1-year absolute uncertainty, tcal ± 5 °C 10 Hz to 10 kHz	± (3 % of p-p output + 100 μV)
Sequence	1-2-5 (eg., 10 mV, 20 mV, 50 mV,...)
Typical dc offset range	0 to ± (≥ 40 % of p-p amplitude) ¹
Frequency	
Range	10 Hz to 100 kHz
Resolution	4 or 5 digits depending on frequency

¹The DC offset plus the wave signal must not exceed 30 V rms.

Pulse Generator Function Specifications

5520A-SC1100 and 5500A-SC600

The pulse generator is designed for oscilloscope capture function tests and trigger verification applications.

Pulse Generator Characteristics	Positive Pulse into 50 Ω
Typical rise/fall times	2 ns
Amplitude available	Discrete steps: 2.5 V, 1 V, 250 mV, 100 mV, 25 mV, 10 mV
Pulse Width¹	
Range	4 ns to 500 ns ¹
Uncertainty ²	5 % ± 2 ns
Pulse Period	
Range	20 ms to 200 ns (50 Hz to 6.6 MHz)
1-year absolute uncertainty, tcal ± 5 °C	± 2.5 ppm

¹Pulse width not to exceed 40 % of period.

²Pulse width uncertainty for periods less than 2 μs are not specified.

TV Trigger Specifications

5520A-SC1100 and 5500A-SC600. TV Trigger is provided at the Scope Output Terminal

Trigger Signal Type	Parameters
Frame formats	Selectable NTSC, SECAM, PAL, PAL-M
Polarity	Selectable Inverted or Uninverted Video
Amplitude into 50 Ω (p-p)	Adjustable 0 to 1.5 V p-p into 50 Ω load, (± 7 % accuracy)
Line marker	Selectable Line Video Marker

Input Impedance Measurement Specifications

5520A-SC1100 and 5500A-SC600

	Range	Uncertainty
Resistance	40 Ω to 60 Ω	0.1 %
	500 kΩ to 1.5 MΩ	0.1 %
Capacitance	5 pF to 50 pF	± (5 % of input + 0.5 pF) ¹

¹Measurements made within 30 minutes of capacitance zero reference. Scope option must be selected for at least five minutes prior to capacitance measurement or zero.

Overload Measurement Specifications

5520A-SC1100 and 5500A-SC600. The overload test function applies dc or ac (1 kHz square wave) power into the 50 Ω oscilloscope input and monitors the current. A time measurement counter indicates the time duration of the applied overload signal. When the oscilloscope's input protection circuit reacts and opens up the 50 Ω load, the calibrator indication is set to "off" on the right hand display. In order to prevent oscilloscope front end damage, a limited amount of energy is applied by a user settable time limit.

Source Voltage	Time Limit dc or 1 kHz ac
5 V to 9 V	Settable from 1 Sec to 60 Sec
Typical "On" Current Indication	Typical "Off" Current Indication
5 V to 9 V	Settable from 1 Sec to 60 Sec

External Frequency Reference Input (5522A only)

The External Reference Input selection allows the user to provide their own high stability 10 MHz reference clock for the 5500A-SC600 and 5520A-SC1100 when fitted in a 5522A mainframe. All functions except Wave Generator and Marker greater than 50ms are then referenced to the external 10 MHz signal. The external reference input must be between 1 V to 5 V p-p.

Uncertainty of output = uncertainty of reference + 5 μHz.

Ordering Information

Models

- 5502A** Multi-Product Calibrator
- 5502A/3** Multi-Product Calibrator with 300 MHz Oscilloscope Calibration Option
- 5502A/6** Multi-Product Calibrator with 600 MHz Oscilloscope Calibration Option
- 5522A** High-Performance Multi-Product Calibrator
- 5522A/6** High Performance Multi-Product Calibrator with 600 MHz Oscilloscope Calibration Option
- 5522A/1GHZ** High Performance Multi-Product Calibrator with 1.1 GHz Oscilloscope Calibration Option


Upgrades of oscilloscope calibration options into 55XX Series calibrators can be done at a Fluke Service Center. Contact a Fluke Service Center or your Fluke Calibration representative for details.

Accessories


- 5500A/COIL** 50-Turn Current Coil
- 9100-200** Dual 10 and 50 Turn Coil
- 55XX/CASE** Roll-Aboard Transit Case
- 5522A/CARRYCASE** Rugged Carrying Case with removable front/back panels
- 5500A/LEADS** Comprehensive Test Lead Kit for 5502A
- 5520A-525A/LEADS** Comprehensive Test Lead Set for 5522A
- 5500A/HNDL** Side Carry Handle
- Y5537** Rack Mount Kit
- MET/CAL®** Calibration Software
- 5800A-7002K** Two Piece Replacement Output Cable Set
- 5800A-7004K** Oscilloscope Calibrator BNC Connector Kit

Product Compatibility Chart

Model	5502A	5522A
5500A-SC300	•	
5500A-SC600	•	•
5520A-SC1100		•



Front view and dimensions.



Side view and dimensions.

Note: 5502A and 5522A dimensions are the same.

Fluke Calibration. Precision, performance, confidence.™

Electrical	RF	Temperature	Pressure	Flow	Software
------------	----	-------------	----------	------	----------



Fluke Calibration
PO Box 9090,
Everett, WA 98206 U.S.A.

Fluke Europe B.V.
PO Box 1186, 5602 BD
Eindhoven, The Netherlands

For more information call:
In the U.S.A. (877) 355-3225 or Fax (425) 446-5116
In Europe/M-East/Africa +31 (0) 40 2675 200 or Fax +31 (0) 40 2675 222
In Canada (800)-36-FLUKE or Fax (905) 890-6866
From other countries +1 (425) 446-5500 or Fax +1 (425) 446-5116
Web access: <http://www.flukecal.com>

©1999-2012 Fluke Corporation. Specifications subject to change without notice.
Printed in U.S.A. 7/2012 1265775G_EN
Pub_ID: 10806-eng, Rev 03S

Modification of this document is not permitted without written permission from Fluke Calibration.