

# Temperature data logger

## MiniVACQ

Temperature data logger for any thermal process from -40°C to +100°C, like pasteurization, storage, washing and disinfection, transportation.




MiniVACQ 1T  
MiniVACQ 1Tc

While being TMI-Orion **entry-level product**, it has a very small size combined to a state-of-the-art technology. The simplified calibration without customized certificate allows an uncertainty of 0.5°C

It is watertight and biocompatible, thus being a good choice for the control of temperature during pasteurization, washing and disinfection processes, storage and transportation.

- 1 internal temperature sensor
- 1 external temperature sensor



### Metrology

- **Operation range:** temperature from -40°C to +100°C
- **Overall calibration uncertainty:** +/- 0,5°C
- **Resolution :** 0.02°C

### Technical specifications

- 316 L stainless steel
- **Dimensions:** Height 39.5 mm / Diameter 15 mm
- **Internal probe:** Pt1000
- **Memory capacity:** 16 000 acquisitions
- **Programmable acquisition rate:** minimum 1 second, maximum 59 minutes and 59 seconds.
- Programmable acquisition duration
- Programmable recording start by date, hour, minute
- User high temperature replaceable battery
- Non volatile memory (EEPROM)

### Software operating conditions

- Data transfer with a communication interface connected to the USB port
- Operates under Windows® XP (SP3)/Vista/7

#### NOTA :

*Annual maintenance is advised for O-rings replacement, recalibration and adjustment.*



TMI-ORION - Parc de Bellegarde - Bât. C - 1, chemin de Borie - 34170 Castelnau-le-Lez - FRANCE  
Tel +33 (0)4 99 52 67 10 - Fax +33 (0)4 99 52 67 19 - [www.tmi-orion.com](http://www.tmi-orion.com)

TMI-USA - 11491 Sunset Hills Rd., Suite 310 - Reston, VA 20190 - USA  
Tel +1 703 668 0114 - Fax +1 703 668 0118 - [www.tmi-orion.com](http://www.tmi-orion.com)